

FULAFLEX 550 PU GREY 835081PM

SAFETY DATA SHEET

REVISION DATE: 10-28-2019 SUPERSEDES: 08-15-2016

SECTION 1: IDENTIFICATION OF THE PRODUCT AND SUPPLIER

PRODUCT INFORMATION

PRODUCT: FULAFLEX 550 PU GREY

PRODUCT DESCRIPTION: Sealant
INTENDED USE: Sealant
PRODUCT IDENTIFIER: 835081PM

COMPANY INFORMATION

H.B. Fuller Company Australia Pty. Ltd.

16 - 22 Red Gum Drive Dandenong South, VIC 3175 Telephone: (03) 9797 6222

Emergency telephone No: 18000 74234 Emergency Tel NZ: 0800 446 881

SECTION 2: HAZARDS IDENTIFICATION

GHS Hazard Symbols:



GHS Symbol name(s): Health Hazard GHS Signal Word: Danger

GHS Classification: Respiratory Sensitisation Category 1

GHS Hazard Phrases: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

GHS Precautions:

Safety Precautions: P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.

In case of inadequate ventilation wear respiratory protection.

First Aid Measures: IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a

position comfortable for breathing. If experiencing respiratory symptoms: Call a

POISON CENTER or doctor/physician.

Disposal: Dispose of contents/container in accordance with local/regional/national/international

regulation for chemical wastes.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS#	PERCENT	Classification	Note
Ethyl acetate	141-78-6	1 - 5	Eye Irrit. 2; H319	
·			Flam. Liq. 2; H225	
			STOT SE 3; H335, H336	
Polymethylene polyphenyl isocyanate	9016-87-9	0.1 - 1	Acute Tox. 4; H332	
			Eye Irrit. 2; H319	
			Resp. Sens. 1; H334	
			Skin Irrit. 2; H315	
			Skin Sens. 1; H317	
			STOT RE 2: H373	



FULAFLEX 550 PU GREY 835081PM

SAFETY DATA SHEET

			STOT SE 3; H335, H336
Methylene bisphenyl diisocyanate (MDI)	101-68-8	0.1 - 1	Acute Tox. 4; H332
			Carc. 2; H351
			Eye Irrit. 2; H319
			Resp. Sens. 1; H334
			Skin Irrit. 2; H315
			Skin Sens. 1; H317
			STOT RE 2; H373
			STOT SE 3; H335, H336
Ingredients determined to be not hazardous		85	

SECTION 4: FIRST AID MEASURES

IF IN EYES: Flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention.

IF ON SKIN: Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists.

IF INHALED: Remove to fresh air. Restore breathing, if necessary. Call a physician if symptoms persist. IF SWALLOWED: Do not induce vomiting. Seek medical attention if symptoms develop. Provide medical care provider with this MSDS.

SECTION 5: FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Use water spray, foam, dry chemical or carbon dioxide.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Material will burn in a fire.

SPECIAL FIRE FIGHTING INSTRUCTIONS: Persons exposed to products of combustion should wear self-

contained breathing apparatus and full protective equipment.

HAZARDOUS COMBUSTION PRODUCTS: Nitrogen containing gases Carbon dioxide, Carbon monoxide

SECTION 6: ACCIDENTAL RELEASE MEASURES

SPECIAL PROTECTION: Exposure to the spilled material may be irritating or harmful. Follow

personal protective equipment recommendations found in Section 8 of this MSDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the

quantity of the spill, the area in which the spill occurred.

SECTION 7: HANDLING AND STORAGE

Handling: Avoid contacting and avoid breathing the material. Use only in a well ventilated

area.

Storage: Store in a cool, dry place.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE LIMITS: AUSTRALIAN EXPOSURE LIMITS ACGIH EXPOSURE LIMITS **Chemical Name** Note Xylene 80 ppm TWA; 350 mg/m3 TWA 100 ppm TWA 150 ppm STEL 150 ppm STEL; 655 mg/m3 STEL Ethyl acetate 200 ppm TWA; 720 mg/m3 TWA 400 ppm TWA 400 ppm STEL: 1440 mg/m3 STEL Polymethylene polyphenyl 0.02 mg/m3 TWA (as NCO, listed under No data available.



FULAFLEX 550 PU GREY 835081PM

SAFETY DATA SHEET

isocyanate	0	(socyanates, all) 0.07 mg/m3 STEL (as NCO, listed under (socyanates, all)	
Methylene bisphenyl diisocyanate (MDI)	Is	0.02 mg/m3 TWA (as NCO, listed under (socyanates, all) 0.07 mg/m3 STEL (as NCO, listed under (socyanates, all)	0.005 ppm TWA (listed under Methylene bisphenyl isocyanate (MDI))

Biological Limit Values (ACGIH)

ſ	Chemical Name	ACGIH Biological Exposure Index (BEI)
ſ	Xylene	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids

ENGINEERING CONTROL METHODS:

VENTILATION: Use local exhaust ventilation or other engineering controls to

minimise exposures.

EYE PROTECTION: Wear safety glasses with side shields when handling this product.

Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Have an eye wash

station available.

SKIN PROTECTION: Avoid skin contact by wearing chemically resistant gloves and long

sleeved shirt. An apron may be appropriate if splashing can occur.

GLOVES: Nitrile

RESPIRATORY PROTECTION: Respiratory protection may be required to avoid overexposure when

handling this product. Use a respirator if general room ventilation is

not available or sufficient to eliminate symptoms.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Semi-solid
COLOR: Grey
ODOR: Characteristic
ODOR THRESHOLD: Not established

pH: Not established FREEZING/MELTING POINT (deg. C): Not established BOILING POINT (deg. C): Not established FLASH POINT: Not applicable EVAPORATION RATE: Not established

FLAMMABILITY: Not a flammable solid or gas

UPPER EXPLOSIVE LIMIT (% in air):

LOWER EXPLOSIVE LIMIT (% in air):

VAPOR PRESSURE (mm Hg):

VAPOR DENSITY:

Not established

Not established

SPECIFIC GRAVITY: 0.000

SOLUBILITY:

OCTANOL/WATER COEFFICIENT:

AUTOIGNITION TEMPERATURE:

DECOMPOSITION TEMPERATURE:

VISCOSITY:

Not established

Not established

Not established

Not established

Not established



FULAFLEX 550 PU GREY 835081PM

SAFETY DATA SHEET

SECTION 10: STABILITY AND REACTIVITY

STABILITY: Stable under normal conditions.

CHEMICAL INCOMPATIBILITY: Strong oxidizing agents

HAZARDOUS POLYMERIZATION: Will not occur.

HAZARDOUS DECOMPOSITION PRODUCTS: Nitrogen containing gases Carbon monoxide, carbon

dioxide

SECTION 11: TOXICOLOGICAL INFORMATION

Component Toxicity / Toxicology Data:

COMPONENT NAME	LD50/LC50
Xylene	Oral LD50 Rat 4,300 mg/kg

This product is a mixture. Unless noted, the information below is based on components.

Skin corrosion / irritation: Can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.

Serious eye damage / irritation: No irritation hazard in normal industrial use.

Respiratory / skin sensitization: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Germ cell mutagenicity: No data available.

Carcinogenicity: No data available.

Reproductive toxicity: Contains a substance that is a probable reproductive hazard based on human studies.

Specific target organ toxicity-single exposure: No data available.

Respiratory irritation / Narcotic effects: No data available.

Specific target organ toxicity-single exposure: No data available.

Target organs potentially affected by exposure: Kidneys Liver Central nervous system Lungs Skin

Aspiration hazard: Not an aspiration hazard.

Medical Conditions Aggravated by Exposure: Liver disease, Kidney disease, Blood disorders (like anemia), Skin disease including eczema and sensitisation, Lung disease, Persons with existing asthmatic conditions may experience difficulty breathing. Persons who have been sensitised to isocyanates may experience symptoms at very low exposure levels.

SECTION 12: ECOLOGICAL INFORMATION

OVERVIEW: No ecological information available for this product.

MOBILITY: No data available.
PERSISTENCE: No data available.
BIOACCUMULATION: No data available.

This product has not been tested for ecological effects. Relevant information for components is listed below:

Component:	Ecotoxicity values:
Xylene	Acute Toxicity (Fish): 96 Hr LC50 Pimephales promelas: 13.4 mg/L [flow-through]; 96 Hr LC50 Oncorhynchus mykiss: 2.661 - 4.093 mg/L [static]; 96 Hr LC50 Oncorhynchus mykiss: 13.5 - 17.3 mg/L; 96 Hr LC50 Lepomis macrochirus: 13.1 - 16.5 mg/L [flow-through]; 96 Hr LC50 Lepomis macrochirus: 19 mg/L; 96 Hr LC50 Lepomis macrochirus: 7.711 - 9.591 mg/L [static]; 96 Hr LC50 Pimephales promelas: 23.53 -
	29.97 mg/L [static]; 96 Hr LC50 Poecilia reticulata: 30.26 - 40.75 mg/L [static] Acute Toxicity (Daphnia): EC50 48 h water flea 3.82 mg/L; LC50 48 h Gammarus lacustris 0.6 mg/L



FULAFLEX 550 PU GREY 835081PM

SAFETY DATA SHEET

Acute Toxicity (Algae): Not established

SECTION 13: DISPOSAL CONSIDERATIONS

This product is a prescribed waste and may only be disposed of in accordance with applicable State and local regulations. These regulations vary from jurisdiction to jurisdiction and hence the user is counselled to seek advice from the local authority and classify the waste before considering disposal. The disposal information given below is a general guide and does not replace the requirement of the local regulations.

DISPOSAL: If possible recycle, otherwise dispose strictly in accordance with local industrial waste or environmental protection regulations. This substance may, if permitted by local authorities, be disposed of in an approved incineration facility or be considered for landfill.

SPECIAL PRECAUTIONS: Do not allow this material to contaminate soil, sewerage systems or surface or ground water.

When large amounts of this product need to be disposed of the services of a registered, professional waste disposal organisation is highly recommended.

SECTION 14: TRANSPORT INFORMATION

Consult Bill of Lading for transportation information.

ADG: NOT REGULATED IATA: NOT REGULATED HazChem Code: Not applicable

SECTION 15: REGULATORY INFORMATION

INVENTORY STATUS

AUSTRALIA AICS: All ingredients in this mixture are listed in the Australian Inventory of

Chemical Substances.

U.S. EPA TSCA: The product contains a substance that is not listed on the TSCA

inventory.

CANADIAN CEPA DSL: This product contains one or more components which have not been

determined to be on the DSL. If you are the importer of this product into Canada, contact H.B. Fuller for chemical tracking and notification

information.

EUROPEAN REACH: As a result of the introduction of REACH into Europe, this product

cannot be imported into Europe unless the REACH requirements are

met.

If you need more information about the inventory status of this product call 1+ 651-236-5858.

Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP):

Exempt

SECTION 16: OTHER INFORMATION

SDS Date of Issue: 28-10-2019



FULAFLEX 550 PU GREY 835081PM

SAFETY DATA SHEET

Replaces: 15-08-2016

Changes made to previous issue: Conversion to GHS format

ACRONYMS and DEFINITIONS:

ACGIH American Conference of Governmental Industrial Hygienists

ADG Code Australian Code for the Transport of Dangerous Goods by Road and Rail

AICS Australian Inventory of Chemical Substances

BEI Biological Exposure Index

CAS Number Chemical Abstracts Service Registry Number

CNS Central nervous system DG Dangerous Goods

Hazchem Code An emergency action code of numbers and letters, which gives information to emergency services.

IARC International Agency for Research on Cancer
IATA Code International Air Transport Association Code
IMDG Code International Maritime Dangerous Goods Code

N.O.S. Not otherwise specified

NOHSC National Health and Safety Commission

PPE Personal protection equipment

SUSMP Standard for the Uniform Scheduling of Medicines and Poisons

UN Number United Nations Number

Prepared by: The Global Regulatory DepartmentPhone: 1-651-236-5842

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to H.B. Fuller Company Australia Pty. Ltd. from its suppliers, and because H.B. Fuller Company Australia Pty. Ltd. has no control over the conditions of handling and use, H.B. Fuller Company Australia Pty. Ltd. makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and H.B. Fuller Company Australia Pty. Ltd. assumes no responsibility for use or reliance thereon. It is the responsibility of the user of H.B. Fuller Company Australia Pty. Ltd. products to comply with all applicable federal, state and local laws and regulations.